




NO.	SYMBOL	
1	BLK	
2	BLA	
3	VLCD	
4	VS+	
5	VS-	220NF
6	VB0-	
7	VB1-	4.7uF
8	VB1+	4.7uF
9	VB0+	
10	VDD	3.3V
11	VSS	
12	TST4	
13	BM0	3.3V/6800
14	CS0	MCU_IO
15	CD	MCU_IO
16	RD	MCU_IO
17	WR	MCU_IO
18	RST	MCU_IO
19	DB0	MCU_IO
20	DB1	MCU_IO
21	DB2	MCU_IO
22	DB3	MCU_IO
23	DB4	MCU_IO
24	DB5	MCU_IO
25	DB6	MCU_IO
26	DB7	MCU_IO
27-34	NC	



*1. LCD Display Type	FSTN,Transflective,positive		
*2. Viewing Direction	6H	*6. Storage Temp	-30°C~80°C
*3. LCD Driver Mode	1/160Duty,1/10Bias	*7. Driver IC	UC1698
*4. Operating Voltage	3.3V	*8. Backlight	WHITE LED IF=3.3v If=75mA
*5. Operating Temp	-20°C~70°C	*9. RDHS	

HOT DISPLAY			
Dwg Title: HTG160160L-31W-34C05-V01			
Dwg No:		Ver: A/0	
Scale 1:1	Unit mm	Tol. ±0.3	
Drawn	Checked	Date: 2020-11-25	